In the Claims:

Claims 1-15 (Canceled).

16. (Currently amended) A method for aligning a spectacle lens comprising:

providing a spectacle lens comprising a machined first side and a second side, the second side of the spectacle lens is secured to a first holder by <u>a first</u> connecting material;

positioning the first holder relative an adapter part, the adapter part comprising an alignment reference and a marking, wherein the positioning comprises aligning the first holder relative the alignment reference; and

aligning said spectacle lens relative a second holder using the marking of the adapter part; and

after the aligning of the spectacle lens relative the second holder, providing a second connecting material to the second holder.

17. (Currently amended) The method as claimed in claim 16 further comprising:

connecting said spectacle lens to said second holder with the second connecting material;

inserting said second holder in a retaining device; and

removing said first holder, said <u>first</u> connecting material and said adapter part from said spectacle lens.

Claim 18 (Canceled).

19. (Previously presented) The method as claimed in claim 16

wherein the positioning of said first holder comprises using a collet chuck in

physical contact with the first holder.

20. (Previously presented) The method as claimed in claim 16

wherein said spectacle lens comprises an organic spectacle lens, and

wherein said organic spectacle lens comprises an organic progressive lens.

21. (Currently amended) An adapter part for aligning spectacle

lenses, the spectacle lenses having a machined first side and a second

side, said second side is provided with a first holder, the adapter part

comprising:

an alignment reference and a collet chuck, the collet chuck in physical

contact with the first holder, the alignment reference and the collet chuck

position said first holder relative said adapter part; and

markings align said spectacle lenses relative other structures; and

wherein said alignment reference comprises a transverse web

extending generally perpendicularly to an optical axis of the spectacle

lenses.

Claims 22-23 (Cancelled).

24. (Currently amended) The adapter part according to claim 22 21 wherein said transverse web is arranged in a cavity in a side of the adapter part.

25. (Previously presented) The adapter part as claimed in claim 24 wherein said markings are provided on another side of the adapter part opposite the side with said cavity.

26. (Currently amended) An adapter part for aligning spectacle lenses, the adapter part comprising:

an alignment reference structure comprising physical material and extending from a surface of the adapter part, the alignment reference structure positions a first holder relative the adapter part; and

markings align said spectacle lenses relative other structures; and

wherein said alignment reference structure comprises a transverse web extending generally perpendicularly to an optical axis of the spectacle lenses.

Claim 27 (Canceled).

28. (Currently amended) The adapter part according to claim 27 26 wherein said transverse web is arranged in a cavity in a side of the adapter part.

 (Currently amended) The method as claimed in claim 16 wherein the positioning of said first holder comprises providing a collet chuck in

physical contact with the first connecting material.

30. (Previously presented) The method as claimed in claim 16 further

comprising releasing the spectacle lens from the adapter part by applying

pressure to the adapter part along an axis parallel to an optical axis of the

spectacle lens.

31. (Previously presented) The adapter part as claimed in claim 21

wherein the collet chuck is in physical contact with the connecting material.

32. (Previously presented) The adapter part as claimed in claim 21

wherein the alignment reference is in physical contact with the first holder.

33. (Previously presented) The adapter part as claimed in claim 26

wherein the markings comprise cross hairs.

34. (Previously presented) The adapter part as claimed in claim 26

wherein the alignment reference structure extends in a single direction.

35. (Previously presented) The adapter part as claimed in claim 26

wherein the alignment reference structure extends across an opening in the

adapter part.

36. (Currently amended) A method of using an adapter part for

aligning spectacle lenses, the method comprising:

providing a spectacle lens comprising a machined first side and a

second side;

securing the second side of the spectacle lens to a holder;

providing an adapter part comprising a collet chuck, the collet chuck

comprising an alignment reference extending generally perpendicularly to an

optical axis of the spectacle lenses; and

aligning the collet chuck relative the holder by physically contacting

the holder and the alignment reference; and

releasing the spectacle lens from the collet chuck by applying

pressure to the collet chuck along an axis parallel to an optical axis of the

spectacle lens.

Claim 37 (Canceled).

spectacle lens during machining of the first side is oriented in a position in a plane perpendicular to an optical axis of the spectacle lens, and wherein the

38. (Previously presented) The method of claim 16 wherein the

aligning using the marking of the adapter part comprises providing the

spectacle lens in the same position in the plane perpendicular to the optical $% \left(1\right) =\left(1\right) \left(1\right) \left($

axis of the spectacle lens.

39. (Previously presented) The method of claim 16 wherein the second side of the spectacle lens is concave, and wherein the connecting

material contacts substantially an entirety of the second side.

40. (Previously presented) The method of claim 16 further comprising providing a protective layer over the second side of the spectacle lens.

41. (Previously presented) The method of claim 16 further comprising providing a plastic film over the second side of the spectacle lenses.

 (Previously presented) The adapter part of claim 21 wherein the markings comprise only two lines intersecting.

43. (Previously presented) The adapter part of claim 26 wherein the markings comprise two lines intersecting at right angles.

44. (Previously presented) The method of claim 36 further comprising spraying a coating over the second side of the spectacle lens.

45. (New) The method of claim 16 wherein the providing of the second connecting material to the second holder further comprises providing the second connecting material simultaneously to the spectacle lens.

46. (New) The method of claim 16 wherein the providing of the second connecting material comprises injecting the second connecting material onto the second holder.

47. (New) The method of claim 16 further comprising removing the first holder together with the first connecting material from the spectacle lens.